



DEALERS & IMPORTERS OF POWER PLANTS & ALLIED MACHINERY

402, 4th Floor, Bezzola Commercial Complex, V.N. Purav Marg, Sion Trombay Road, Chembur, Mumbai – 400071, INDIA.

Tel: Off : +91 22 2523 4478 / 67973677
Fax : +91 22 2523 5386
E mail : enquiry@corponit.com
Website : www.corponit.com

1 No. 2.5 MW APE Belliss make Back Pressure type Steam Turbine Generator Set :

Multistage back pressure type Steam turbine, frame BD-2 APE BELLISS 1993 make, speed 6000 RPM, OUTPUT 2500 Kw.

Operating Parameters	Max.	Nor.	Min.
Inlet steam pressure – Kg/Cm ²	32	30	28
Inlet steam temperature oC.	390	370	350
Exhaust steam pressure Kg/Cm ²	1.5	1	0.5

Branch Size:

- a) Inlet = 6" dia.
- b) Exhaust Size = 18" dia
- c) Rotation = Clockwise when looking from governor end of turbine

HIGH SPEED REDUCTION GEAR BOX:

- Make = WIL
- Type = GN-40
- Ratio = 6000:1500 (4:1)
- Service Factor = 1.5
- Power = 2500 kW

GENERATOR:

Make	=	KIRLOSKAR
Frame	=	A 4B 710/6
Machine No.	=	9341004-01
kVA	=	3125
Rating	=	SI TO IS 4722-1992
Extr-AC		
Insulation Class	=	ST-F, RT-F
EX-F	=	0.8
Volt	=	100 V
EXTN Current	=	3 AMS
Phase	=	3
Lube oil	=	Turbinol 46

ACCESSORIES:

Main control panel, Turbine Control panel, Oil Coolers, Generator Air Cooler, Governing Valve Body, etc. as available at site

NITIN CORPORATION